

PRG

Rolling Stage

PRG Rolling Stage is a flexible, portable stage that offers strength and durability and is also quick to assemble.

Quality Assurance

Engineered for safe, efficient, and rapid deployment and is easily re-positioned and reconfigured.

Product Options

The design is based on a standard 4' x 8' (1.22m x 2.44m) size with additional options for configuration. PRG's Rolling Deck is ideal for all markets including corporate events, concert touring, television, and theatre.

Queen with Adam Lambert Tour 2014


PRG Rolling Stage



Standard Plywood Platforms

Platform Size	Ecode
4' x 8'	2.90531-101
4' x 6'	2.90531-111
4' x 4'	2.90531-121
2' x 8'	2.90531-131
2' x 4'	2.90531-141


Custom configurations available. Call for details.



Black Vinyl Lid Platforms

Platform Size	Ecode
4' x 8'	2.90531-102
4' x 6'	2.90531-112
4' x 4'	2.90531-122
2' x 8'	2.90531-132
2' x 4'	2.90531-142

Custom configurations available. Call for details.



Grating Lid Platforms

Platform Size	Ecode
4' x 8'	2.90531-103
4' x 6'	2.90531-113
4' x 4'	2.90531-123
2' x 8'	2.90531-133
2' x 4'	2.90531-143

Custom configurations available. Call for details.



Guardrail (Black Anodized)

Size	Ecode
3' Guardrail	2.90531-403
4' Guardrail	2.90531-404
5' Guardrail	2.90531-405
8' Guardrail	2.90531-408

Custom configurations may be available. Call for details.



Guardrail (Polycarbonate)

Size	Ecode
4' Guardrail	
8' Guardrail	

Custom graphics/privacy panels are available upon request.



Adjustable Handrail for Stairs

Handrail Height	Ecode
36" – 56"	2.90531-443
48" – 72"	2.90531-444

Custom configurations may available. Call for details.



Adjustable Step Unit

Stair Height	Ecode
24" – 36"	2.90531-422
36" – 56"	2.90531-423
48" – 72"	2.90531-424

Custom configurations may available. Call for details.




Stage Skirting (Black)

Size	Ecode
2'H x 26.5' W	2.90531-726
3' H x 25' W	2.90531-735
5' H x 25' W	2.90531-755
6' H x 25' W	2.90531-765

Additional sizes may be available. Call for details.

PRG Rolling Stage



Straight Legs

2' Straight Leg	2.90531-202
3' Straight Leg	2.90531-203
3'-6' Straight Leg	2.90531-213
4' Straight Leg	2.90531-204
5' Straight Leg	2.90531-205
6' Straight Leg	2.90531-206
8' Straight Leg	2.90531-208

Bent Legs





4' Bent Leg	2.90531-254
5' Bent Leg	2.90531-255
6' Bent Leg	2.90531-256
8' Bent Leg	2.90531-258

Leg Brace

For 2' Deck	2.90531-332
For 3' Deck	2.90531-333
For 4' Deck	2.90531-334
For 5' Deck	2.90531-335
For 6' Deck	2.90531-336
For 8' Deck	2.90531-338

Locator Plates

Size	Ecode
Locator Plate x1	2.90531-310
Locator x2 Left	2.90531-320
Locator x2 Right	2.90531-321
Locator Plate x3	2.90531-330
Locator Plate x4	2.90531-331



20' Circular Platform Assembly

Size	Ecode
20' Diameter	2.90916-10

16' Circular Platform Assembly

Size	Ecode
16' Diameter	2.90913-10

Apron

Size	Ecode
162' Radius	2.90911

Monitor Shelf

Size	Ecode
162' Radius	2.9091H

Custom configurations may be available. Call for details.

PRG Rolling Stage Data Sheet



PRG Rolling Stage is a flexible, portable stage that offers strength and durability and is also quick to assemble. The Rolling Stage is engineered for safe, efficient and rapid deployment and is easily repositioned and reconfigured. The design is based on a standard 4'x8' (1.22m x 2.44m) size.

PRG's Rolling Stage is ideal for all markets including corporate events, concert touring, television and theatre. The Rolling Deck is designed with a heavy-duty leg and caster system that is available in 4', 5', 6' and 8' heights so there is no need to wrestle with unstable adjustable legs. A heavy-duty threaded-rod leveling feature engineered into the casters provides precise leveling of the stage deck. The heavy-duty legs easily lock into place with a slip pin and are available in either a straight or bent version. Bent legs allow for conflict-free joining of platforms during fast reconfigurations. Platforms are placed on legs fitted with either single, double or quad mounting pin nodes for joining Rolling Stage sections. The innovative mounting pin node means that extraneous legs are removed from the set-up without compromising safety or stability. This unique leg system requires minimal crew for installation and repositioning. The legs lock into place with a slip pin mechanism and require no tools for attaching or detaching. Diagonal supports, which are all the same length, also mount with a slip pin mechanism and require no tools for attaching or detaching. All PRG Rolling Stage platforms Roto-Lock from underneath for quick and easy assembly of large stage decks.

Features

Quick and Easy Assembly

- Extruded aluminum frame design
- Platform constructed of plywood top over an aluminum skin
- Aluminum skin provides a Class-A fire rating for the platform
- Smooth rolling motion allows easy reconfiguration with minimal crew
- Standard 4' X 8' (1.22m X 2.44m) platform allows for flexible size configurations
- Each 4' X 8' deck supports up to 120 Lbs/Sq-Ft
- Casters available in standard-duty or heavy-duty sizes
- Stock legs are available in 4', 5', 6', and 8' heights
- Legs are available in either straight or bent versions and lock easily into place with a slip pin lock
- The bent legs allow sections to be brought quickly together without conflict when the deck needs to be reconfigured while in use
- Straight legs and mounting pin nodes join stationary sections quickly and safely
- Single, double or quad nodes top plates on a single leg offer fast, flexible assembly and cut down on unnecessary legs
- Same length diagonal supports reduce the need for extra components and save assembly time
- Diagonals easily mount with slip pin locks
- Rounded platform rail edges allow for easy, safe handling
- Platform sections roto-lock from underneath for faster assembly
- Casters using a threaded rod allow for fast, precise leveling on uneven floors
- Easily attached staircase is adjustable for height and pitch
- Accessory handrail sections easily lock into the side and end rails of the platforms